


IN120126**INDUCTIVE SENSORS • ENLARGED SWITCHING DISTANCE**

Inductive proximity switches are contact-free sensors. They detect all conductive metals, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material and its dimensions. The vibration-resistant sensors can be approached laterally or frontally. Inductive proximity switches are used for presence detection (e.g. goods carriers), positioning (e.g. dampers), counting (e.g. nuts /bolts), speed detection (e.g. for cog wheels), on conveyor systems (e.g. hose feedings) or distance measurements (e.g. press-in checking) of metallic objects.


**TECHNICAL DATA**

2x increased switching distance	No
3x increased switching distance	Yes
4x increased switching distance	No
Ambient temperature	-25 °C ... 70 °C
Ambient temperatures < -25°C	No
Areas inquiry	No
Atmospheric-change resistant (temperature cycle)	No
Cascadable	No
Connection to amplifier	No
Correction factor (aluminum)	0.4
Correction factor (brass)	0.56
Correction factor (copper)	0.45
Correction factor (stainless steel)	0.77
Correction factor (steel)	1
Degree of protection (IP)	IP67
Devices for hose mounting	No
Distance measuring sensors	No
End position sensing, hydraulic cylinder	No
Feeding technology	No
Harsh environmental conditions	No
High-pressure-proof sensors	No
Housing coating	Chromium-plated
Housing design	Cylinder, screw-thread
Housing material	Brass
Hygienic and wet area	No
Hysteresis	10 %
Increased ambient temperatures > 80°C	No
Increased switching distance	Yes
Material independent sensors (factor 1)	No
Max. output current	200 mA

TECHNICAL DATA

Mechanical mounting condition for sensor	Not flat
Metallic sensor surface	No
No-load current	10 mA
Norm measuring plate	30x30x1
Number of pins	3
Oil and cooling lubricants	No
Pressure-proof	No
Rated control supply voltage U_s at DC	10 V ... 30 V
Relative repeat accuracy	3 %
Reverse polarity protection	Yes
Ring-shaped sensors	No
Sensor length	60 mm
Short-circuit-proof	Yes
Suitable for safety functions	No
Supply voltage	10 V ... 30 V
Switching distance	10 mm
Switching frequency	400 Hz
Teflon housing	No
Thread length	35 mm
Thread pitch	1 mm
Thread size, metric	12
Type of electrical connection	Connector M12
Type of switching function	Normally open contact
Type of switching output	PNP
Voltage drop	2 V
Voltage type	DC
Welding area	No
Welding-proof sensors	No
With LED display	Yes
With monitoring function of downstream devices	No


CONNECTION



Colors: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

Functions: 1 = L+, 2 = n. c., 3 = L-, 4 = PNP NO

DIMENSIONAL DRAWING



INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.