

MW991424

•

For length measurement, rotational speed or angle measurement, magnetic measuring systems are used. These systems operate in a way that the sensor moves without contact over a flexible magnetic tape, or it is situated above the rotating magnetized measuring wheel. The magnetic tape is applied to a 0.3mm thick steel strip and is located on the circumference of the various measuring wheels. The magnetization is carried out with defined pole pitches. By scanning of the magnetic poles an analog signal is generated, which is converted into digital square wave signals that can be processed by a downstream electronics and, if necessary, be displayed. The sensor detects the pitch of the strip and converts the information into a high-resolution path or rotation information. To read out the ma-



gnetic lines no direct contact is required. Magnetic sensors are insensitive to dirt, oils and moisture and relatively stable at shock and vibration. For users, this opens up a wide field of applications, e.g. for plants and systems in the timber industry, at linear axes, in outdoor areas or with machine tools.

TECHNICAL DATA

TECHNICAE DAIA	
Absolute linear measurement	No
Absolute measurement	No
Ambient temperature	0 °C 60 °C
Battery-powered systems	No
Cable length	3 m
Degree of protection (IP)	IP67
Housing material	Aluminium
Large sensing range	No
Length	26.7 mm
Material of cable sheath	PVC
Max. traverse speed	5 m/s
Multi-part systems	Yes
Number of pins	6
Relative air humidity	100 %
Resolution	10 μm
Reverse polarity protection	No
Sensing range	0.1 mm 2 mm
Sensor height	15 mm
Sensor length	26.7 mm
Sensor width	7.8 mm
Shock resistance, acceleration	200 G
Shock resistance, pulse time	11 ms
Short-circuit-proof	No
Storage temperature	70 °C
Storage temperature	-20 °C
Suitable for absolute value detection	No
Track A inverted	No



TECHNICAL DATA

Track B inverted	No
Type of electrical connection	Cable with connector
Vibration resistance, acceleration	20 G
Vibration resistance, frequency	50 Hz
With LED display	No
With communication interface, SSI	No
With display	No
With reference signal	No
With reference signal track	No

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!



DISPOSAL

SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!