



## Type 2850 Conductivity/Resistivity Sensor Electronics

### Conductivity/Resistivity:

- Accepts any cell constant
- Compatible with all Signet Conductivity Sensors
- Output choices include digital (S<sup>3</sup>L) for use with the Signet 8900, 9900, 9950 or 4 to 20mA
- Compatible with Signet Instrument Type 8900 or instruments accepting a 4 to 20mA output
- Single or dual input available for remote mount version (S3L) only

MFR #	Mounting	Output	Code
3-2850-51	3/4 inch FNPT	Digital (S3L), one input	<b>159 001 398</b>
3-2850-52	3/4 inch FNPT	4 - 20mA, one input	<b>159 001 399</b>
3-2850-61	Universal Mount	Digital (S3L), one input	<b>159 001 400</b>
3-2850-62	Universal Mount	4 - 20mA, one input	<b>159 001 401</b>
3-2850-63	Universal Mount	Digital (S3L), one or two inputs	<b>159 001 402</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>