


Inductive proximity switches are contact-free sensors. They detect all conductive metals, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material and its dimensions. The vibration-resistant sensors can be approached laterally or frontally. Inductive proximity switches are used for presence detection (e.g. goods carriers), positioning (e.g. dampers), counting (e.g. nuts /bolts), speed detection (e.g. for cog wheels), on conveyor systems (e.g. hose feedings) or distance measurements (e.g. press-in checking) of metallic objects.



TECHNICAL DATA

Devices for hose mounting	NO
Feeding technology	NO
Harsh environmental conditions	NO
Hygienic and wet area	NO
Metallic sensor surface	NO
Oil and cooling lubricants	NO
Ring-shaped sensors	NO
Welding-proof sensors	NO
Ambient temperature (min/max)	-25 °C / 70 °C
Ambient temperatures < -25°C	NO
Atmospheric-change resistant (temperature cycle)	NO
Cable length	2 m
Degree of protection (IP)	IP67
High-pressure-proof sensors	NO
Housing coating	Nickel-plated
Housing design	Cylinder, screw-thread
Housing material	Brass
Housing material	Metal
Increased ambient temperatures > 80°C	NO
Material independent sensors (factor 1)	NO
Material of cable sheath	PVC
Mechanical mounting condition for sensor	Concise
Number of wires	2
Pressure-proof	NO
Sensor length	82 mm
Teflon housing	NO
Thread length	61 mm
Thread pitch	1 mm
Thread size, metric	18
2x increased switching distance	NO
3x increased switching distance	NO

TECHNICAL DATA

4x increased switching distance	NO
Cascadable	NO
Connection to amplifier	NO
Correction factor (aluminum)	0.3
Correction factor (brass)	0.4
Correction factor (copper)	0.2
Correction factor (stainless steel)	0.7
Correction factor (steel)	1
Distance measuring sensors	NO
Hysteresis	15 %
Increased switching distance	NO
Max. output current	400 mA
No-load current	15 mA
Norm measuring plate	18x18x1
Rated control supply voltage U_s at AC 50HZ (min/max)	20 V / 250 V
Relative repeat accuracy	10 %
Reverse polarity protection	NO
Short-circuit-proof	YES
Suitable for safety functions	NO
Supply voltage (min/max)	20 V / 250 V
Switching distance	5 mm
Switching frequency	10 Hz
Type of electrical connection	Cable
Type of switching function	Normally open contact
Type of switching output	AC
Type of switching output	Two-wire
Voltage drop	5 V
Voltage type	AC
With LED display	YES
With monitoring function of downstream devices	NO
Areas inquiry	NO
End position sensing, hydraulic cylinder	NO
Welding area	NO

CONNECTION



Colors: BU (blue), BK (black)

Functions: BU = L+, BK = L-

DIMENSIONAL DRAWING

