

high performance through-beam sensors and amplifiers

Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.




TECHNICAL DATA

Scope of delivery of the one-way system	Receiver
Ambient temperature (min/max)	-25 °C / 60 °C
Degree of protection (IP)	IP67
Housing design	Cylinder, screw-thread
Housing material	Stainless steel
Increased ambient temperatures >70°C	NO
Sensor length	66 mm
Shock resistance	30 G
Thread length	40 mm
Thread pitch	1 mm
Thread size, metric	12
Vibration resistance	55 Hz
Alarm output	NO
Connection to amplifier	NO
Function test	NO
Input (TeachIn)	NO
Max. output current	100 mA
Measuring range	15 m
No-load current	30 mA
No-load current, receiver	30 mA
Number of pins	3
Operating voltage (min/max)	15 V / 30 V
Rated switching distance	15000 mm
Reverse polarity protection	YES
Scanning function	Dark switching
Short-circuit-proof	YES
Switching frequency	25 Hz
Type of electrical connection	Connector M12

TECHNICAL DATA

Type of input voltage	DC
Type of switching function	Other
Type of switching output	PNP/NPN
Voltage drop	2 V
Voltage type	DC
With LED display	YES
With time function	NO
Heavy-duty devices	YES
Angle of beam spread	12 °
Light beam form	Point
Light source	Infrared light
Wavelength of the sensor	880 nm

CONNECTION



Colors: A: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)
 B: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)
Functions: A: 1 = L+, 2 = n. c., 3 = L-, 4 = PNP NO
 B: 1 = L+, 2 = n. c., 3 = L-, 4 = NPN NC

DIMENSIONAL DRAWING